

# EVB-LAN8187

## LAN8187(I) RMII Customer Reference Design

+1.8V I/O VDDIO Operation

Schematic Revision B4

### Design Details

Board: PCB-7058RAZ-LV

Chip: LAN8187(I)


Board Form Factor:

Assembly:

Circuit Diagrams utilizing SMSC Products Are Included As A Means Of Illustrating Typical Semiconductor Applications: Consequently Complete Information Sufficient For Construction Purposes Is Not Necessarily Given. The Information Has Been Carefully Checked And Is Believed To Be Entirely Reliable. However, No Responsibility Is Assumed For Inaccuracies. Furthermore, Such Information Does Not Convey To The Purchaser Of The Semiconductor Devices Described Any License Under The Patent Rights Of SMSC Or Others. SMSC Reserves The Right To Make Changes At Any Time In Order To Improve Design And Supply The Best Product Possible.

### EVB BLOCK DIAGRAM

This reference design is targeted to meet a +1.8V IO voltage range.




ITEM	Page
Title Page	1
Stackup	2
LAN8700(I) & Magnetics	3
Power & Misc	4

Revisions	
Rev B4 Public 11/2/06	change center tap of magnetic to 75 ohms; corrected name on pin 1 to RMII; moved nINTTXERTXDM on symbol; added pulldown to nINT; moved caps from page 4 to page 3; removed 150ohm DNP R63 & R64; increased the 1000pF RJ45 capacitors to 2kV; added 100ohm series resistor to XTAL.



Title			
EVB-LAN8187_RMII_BD_LV			
Size	Document Number	Rev	
C	SCH-7058RAZ-LV	B4	
Date:	Thursday, November 30, 2006	Sheet	1 of 4

# stackup




## NOTES:

- BOARD FABRICATION AND QUALITY ACCEPTANCE PER IPC-6012 CLASS 2. BOARD MUST MEET OR EXCEED QUALIFICATION TESTING AND QUALITY CONFORMANCE TESTING INSPECTION SPECIFIED WITHIN.
- MATERIAL: NEMA GRADE STANDARD FR4 LAMINATED SHEET; HTE 1 OZ COPPER CLAD, TYPE GF/GF2 WOVEN GLASS BASE; FLAME RESISTANCE MEETING UL94V-0 OR BETTER. MATERIAL IN ACCORDANCE WITH IPC-4101.
- BOARD FABRICATION SHALL APPLY DATE CODE, FABRICATOR'S CAGE CODE, I.D. AND UL MARKING TO SECONDARY SIDE WHERE INDICATED. MARKING PREFERABLY COPPER ETCHED, EPOXY INK ACCEPTABLE.
- SOLDERMASK USING TYPE B PHOTO IMAGEABLE LPI FILM 0.0015 THICK. APPLY TO BOTH SIDES IN ACCORDANCE WITH IPC-SM-840 (TYPE B CLASS 3). USE APPROPRIATE SOLDER MASK ARTWORK FOR EACH SIDE. PUNCTURING OF PUNCTURING OF TENDED HOLES IS PERMISSIBLE. SOLDERMASK MISREGISTRATION SHALL NOT EXCEED .004 INCH. SOLDERMASK OVERLAP PERMITTED ON CIRCULAR LANDS ONLY AND SHALL NOT EXCEED 0.001 INCH. NO OVERLAP PERMITTED ON RECTANGULAR LANDS.
- FINISH: SOLDER MASK OVER BARE COPPER (SMOBC), HOT AIR LEVEL DEPOSIT ABOUT TRUE POSITION.
- DRILL BOARDS USING DRILL DATA, DRILL PATTERN AND HOLE SCHEDULE. HOLE LOCATION MAY VARY WITHIN .004 IN. MAX.
- MINIMUM ANNULAR RINGS:  
.002 IN MINIMUM - EXTERNAL LAYERS.  
.001 IN MINIMUM - INTERNAL LAYERS.
- ALL EXPOSED SURFACE LANDS AND LINES TO BE SOLDER COATED.
- ALL HOLES ARE PLATED THROUGH UNLESS NOTED OTHERWISE. MINIMUM COPPER PLATING IN PLATED HOLES TO BE .001 IN. COPPER PLATING IN TENDED HOLES SHALL NOT PLUG HOLES WITHOUT PERMISSION FROM SMSC.
- COMPONENT MARKINGS: SILKSCREEN BOTH SIDES USING NON-CONDUCTIVE WHITE EPOXY INK. LANDS AND EXPOSED PLATED AREAS TO BE FREE OF INK.
- DIMENSIONS ARE AFTER ETCHING AND PLATING AND ARE BASIC UNLESS OTHERWISE INDICATED.
- BARE BOARD ELECTRICAL TEST: BARE BOARDS SHALL BE ELECTRICALLY TESTED USING CAD GENERATED NET LIST DATA. THIS INFORMATION TO BE SUPPLIED IN IPC-D-350 FORMAT. ELECTRICAL TESTING SHALL FOLLOW THE GUIDELINES ESTABLISHED BY IPC-ET-652, GUIDELINES AND REQUIREMENTS FOR ELECTRICAL TESTING OF PRINTED WIRING BOARDS.



Title		EVB-LAN8187_RMII_BD_LV	
Size	Document Number	Rev	
C	SCH-7058AZ	B4	
Date:	Thursday, November 30, 2006	Sheet	2 of 4



Mode 2 R48	Mode 1 R49	Mode 0 R50	Boot Strap Options
Empty	Empty	Empty	111 All Capable (Default)
Empty	Empty	Populated	110 Power Down Mode
Empty	Populated	Empty	101 Repeater Mode
Empty	Populated	Populated	100 100Base-TX Half duplex Advertised
Populated	Empty	Empty	011 100Base-TX Full Duplex Auto Negotiate
Populated	Empty	Populated	010 100Base-TX Half Duplex Auto Negotiate
Populated	Populated	Empty	001 10Base-T Full Duplex Auto Negotiate
Populated	Populated	Populated	000 10Base-T Half Duplex Auto Negotiate

PHY_address	LED Output	Resistor configuration
SPEED100PHYAD0	LSB PHYAD0 = 1	Default: Active Low; Populate R24 Depopulate R31 LED2 orient up
LINKPHYAD1	LSB PHYAD1 = 0	Default: Active High; Populate R31 Depopulate R24 LED2 orient down
	PHYAD1 = 1	Default: Active Low; Populate R37 Populate R24 Depopulate R38 Depopulate R34
	PHYAD1 = 0	Default: Active High; Populate R38 Populate R34 Depopulate R37 Depopulate R29
ACTPHYAD2	PHYAD2 = 1	Default: Active Low; Populate R35 Populate R32 Depopulate R36 Depopulate R33
	PHYAD2 = 0	Default: Active High; Populate R36 Populate R33 Depopulate R35 Depopulate R32
FDUPLXPHYAD3	PHYAD3 = 1	Default: Active Low; Populate R27 Depopulate R28 LED3 orient up
	PHYAD3 = 0	Default: Active High; Populate R28 Depopulate R27 LED3 orient down
GPO1PHYAD4	MSB PHYAD4 = 1	Default: Active Low; Populate R25 Depopulate R26 LED1 orient up
	MSB PHYAD4 = 0	Default: Active High; Populate R26 Depopulate R25 LED1 orient down

VDDIO Voltage	Config Strapping resistors (Ohms) R59 R45 R52 R46 R56 R47 R53 R44 R58 R50 R51 R43 R49 R41	LED Resistors (Ohms) R24 R32 R27 R25 R26 R28 R29 R30 R33 R31 R69
3.6	10k	330
3.0		
2.0	7.5k	226
1.8		
1.6	5k	150

Mode 2 R48	Mode 1 R49	Mode 0 R50	Internal +1.8v regulator: Populate R58 De-populate R59 Enable Populate R59 De-populate R58 Disable
Empty	Empty	Empty	Populate R58 De-populate R59 Enable
Empty	Empty	Populated	Populate R59 De-populate R58 Disable

\* Note: The (I) designates industrial temperature LAN8187I PHY (-40c to +85c). For industrial temperature applications, SMSC recommends using the LAN8187I with industrial temperature magnetics. For Commercial temperature magnetics, capacitor C30 and C31 can be de-populated. Please refer to APP note 8.13 Magnetics Selection Guide \*




3930 East Ray Road  
Suite 200  
Phoenix, Arizona 85044  
480-759-0200

**EVb-LAN8187\_RMII\_BD\_LV**


Document Number: **SCH-7058AZ**

Date: Friday, December 01, 2006 Sheet 3 of 4

### +5V MII to +3.3V Regulator



### +5V MII to +1.8V VDDIO Regulator



For +1.8V IO, R63 = 56ohm  
 For +2.5V IO, R63 = 124ohm  
 For +3.3V IO, R63 = 205ohm

